



4SURE TRAILERS LTD

6 Fleming Road, Earlstrees Ind. Estate,
Corby, Northants, NN17 4SW.

Tel: 01536 202 944 Fax: 05601 166 993

ST Trailer vs GT Trailer - The benefits of upgrading.

<u>THE ST TRAILER</u>	<u>THE GT TRAILER</u>
Internal trailer body width of 1.98M (6'6").	Upgraded trailer width to 2.13M (7')* internally.
N/A	* Can be increased further to 2.44M (8') if towed by vehicle larger than 3500Kgs.
22mm thick Gloss white GRP insulated composite body panels with timber perimeter inserts for added strength.	Upgraded 35mm thick gloss white GRP insulated composite body panels with high density foam perimeter inserts for additional strength which are lighter than timber and have moisture resistant properties.
Tandem axle trailer with Gross trailer weight of 2600Kg.	Gross trailer weight upgradable to 3500Kgs on a tandem (as standard) or tri axle configuration.
Simple Locking 'T' handles and slam locks fitted to access door. S/steel shoot bolts to hatch.	Hard wearing 5-lever locks fitted to all doors and hatches for added security
Removable fibreglass (shell) 'lift-off' gas box to cover 2 x 19Kg bottles	Solid 22mm GRP composite gas locker housing fitted with locking 'T' handle and budget lock. Houses 2x 19Kg bottles (which is upgradable).
Approved Black painted heavy duty chassis - (requires re-painting as necessary)	Approved Hot Dip Galvanised chassis for added protection (heavy duty). 'Maintenance free'.
No wheel arch infill covers provided as standard.	Removable wheel arch infill covers fitted to trailer as standard.
22mm GRP fold down customer shelf	Recessed stainless steel fold down customer shelf
Independent hatch sign board panel fitted to serving hatch which can be sign written to your choice.	Bi-folding' hatch signboard panel, integral part of the design and prevent rain water running directly off the front edge protecting your clients.
No filling tap available as standard.	Hot water filling tap fitted directly to fill tea urn which is integral to the 230v water system.
Heavy duty stainless steel worktops finished with anodised aluminium trim exclusive to 4Sure.	Same worktop available as standard, however the option of full 'rolled edge' worktop available with GT
2 x Front clear marker light and 2x rear cluster lamp fitted as standard for towing.	As per ST trailer also fitted with 2x additional high level rear marker lights to outline the trailer.
All the following items are also included within the standard specification of 4 Sure's Catering trailer ranges (both the ST and GT):	
230volt (or 12volt) pressure sensitive water pump	1x Double door cupboard area under sinks
L.P.G or 230 Volt water heater	20Ltr Burco Dean L.P.G deluxe boiler
18mm thick phenolic chemical resistant flooring	4 x Heavy duty corner steadies
Red or Blue non-slip lino floor covering	25 Ltr Fresh water container
2x Round stainless steel sinks	23 Ltr Waste water container
230v electrical installation with 2x skt and 2x light	12 Month N.I.C.E.I.C Electrical installation certificate
230v / 16A electrical trailing extension lead	6 Month Gas Safe safety certificate
2 Year warranty on materials supplied by 4Sure	12month labour back to base warranty on trailer